



The Right Connection®

Dixon Sanitary Valve Automation

Featuring Dixon Sanitary™ ball and butterfly valves with remote indication



BV2CV-150CC-LB
1/2" to 4"
(Ball Valve)

B5101S200CC-LJ
1" to 8"
(Butterfly Valve)

Limit Switches on a manual valve allows verification of valve position (open/closed) remotely and reduces labor costs by creating efficiencies in plant operations

Ball Valves

- Stainless and Brass
- Industrial and Sanitary
- 2 & 3 piece
- 2, 3, & 4 way
- Seals: virgin PTFE, 15% glass, 50% stainless, UHMW. (A) & 25% carbon

Butterfly Valve

- Handles: pull, push ccw, push cw, infinite & trigger
- Seat Materials: silicone, EPDM, FKM
- Body Styles: 5101, 5102 & 5104 series

Features and Benefits

- Intermediate and proportional feedback
- Position detection can be determined using various switches & enclosures
- End configurations: clamp, butt-weld, bevel seat, John Perry, I-line, Q-line, NPT and FNPT

All systems are 100% inspected and tested
Most systems ship within 24 hours from Wisconsin

Dixon Sanitary

N25 W23040 Paul Road Pewaukee, WI 53072
ph: 800.789.1718 • fx: 800.789.4046
dixonvalve.com